

Pro-Seal Anti-Graf™



Non-Sacrificial Polycarbon/Polycarbonate Anti-Graffiti Sealer

Description

Pro-Seal Anti-Graf™ is a Polycarbon/Polycarbonate graffiti and hydrocarbon resistant sealer. When used with Pro-Seal De-Graf™, Pro-Seal Anti-Graf™ is non-sacrificial.

Advantages

- Environmentally friendly
- May be custom tinted to match existing painted surfaces
- Easy to apply
- Will not alter color or texture of applied substrate
- Creates a simple solution to a usually costly problem, remove graffiti with ease in minutes!
- No V.O.C.

Uses

- Concrete
- Brick
- Metal
- CMU Block
- Stucco

Application

1. Surface must be dry, clean and free of all loose particulate and bond-breaking matter.
2. Apply the first coat of Anti-Graf™ to substrate at a coverage rate of ~350 square feet per gallon in a horizontal pass.

3. Allow the first coat to dry to touch.
4. Apply the second coat of Pro-Seal Anti-Graf™ at a coverage rate of ~ 350 square feet per gallon in a vertical pass.
5. Allow second coat to dry to touch.
6. This product is a pre-treatment for surfaces not yet vandalized. For graffiti removal instructions, refer to the Pro-Seal De-Graf™ technical data sheet.
7. For specific application instructions or guide specifications, contact us at 425.482.1671 or information@prosealproducts.com

Technical

| Information | Value |
|-------------------------|-------------------------------------|
| Material | 1 part |
| Mix time | N/a |
| Appearance | Liquid |
| Application | See guide specification |
| Cure time to touch | 2 hours |
| Cure to hard | 8 hours |
| Full cure | 96 hours |
| Stain resistance | Excellent |
| Application temperature | >50°F |
| Color | Clear, may be custom colored |
| Packaging: | 1 gallon 5 gallons 55 gallons |

Technical Support

For technical support, contact our toll-free technical hotline at 425.482.1671 or information@prosealproducts.com



Pro-Seal Anti-Graf™



Non-Sacrificial Polycarbon/Polycarbonate Anti-Graffiti Sealer

Cautions

Keep out of reach of children. May cause skin or eye irritation. May be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.

Pro-Seal Anti-Graf™



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 425.488.6570 • Fax: 425.488.6926 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal