

Pro-Seal Drycrete™

Polycarbon/Polycarbonate Bonding And Drying Agent



Drycrete™ is a bonding and drying agent for concrete that may cure some new concrete uniformly while resisting spot drying and hair checking. *Polycarbon/polycarbonate integrated technology

- Does not alter color or texture of concrete
- Preserves most concrete surfaces
- One coat application
- Retards some hydrostatic head
- Reduces seepage
- Provides a prepared surface for paint, extending paint life
- Properly installed, provides excellent bonding between concrete slabs
- Permanently hardens and densifies concrete surfaces
- Prevents dusting

Applications: Vertical & Horizontal Concrete Applications, Existing Concrete, New Concrete, Between Concrete Slabs and Bonding Agent for polycarbon/polycarbonate grouts & patches

Application Instructions: Apply product using a simple 20-30 psi low-pressure sprayer at a coverage rate of 200-600 square feet per gallon depending on substrate. In areas where seepage exists, DP-36® may be required. For specific application instructions or guide specifications, contact us at 800.349.7325 or information@prosealproducts.com.

Technical

Information	Value
Material	1 part
Appearance	Liquid
Application temp	> 42°F to <220°F
Storage temp	> 32°F to < 98°F
Coverage rate	200-600 ft ² / gallon
Dry time	2-4 hours
Packaging	Quart, 1, 5 and 55 gallons

Technical Support: Contact our technical department at 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information

Specifications

Concrete Specimens Tested as Follows		
ASTM	Data	Value
C 67 Section 7	Decreased Absorption	25%
C 67 Section 14	Decreased Suction	35%
C 67 Section 10	Efflorescence	None
C 67 Section 6	Compressive Strength	@ 8 Days +15%
C 67 Section 6	Compressive Strength	@ 31 Days +23%
C 156	Concrete curing against hairline cracking & spot drying	Significant Improvement
C 666	Freeze-Thaw Damage	75% Improved Resistance
C 666 using 5% Nacl	Salt Attack In Presence Of Moisture	60% Improved Resistance
Orf Method	Dusting Due To Abrasion	100% Improved Resistance
C 39	Hardening increase	35%
G 2381	Weathering	Opaque to U.V. under 2800 U.A. no adverse effect

Cautions: Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty: We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.

