

Pro-Seal Drycrete™



Polycarbon/Polycarbonate Bonding And Drying Agent

Product Description

Pro-Seal Drycrete™ is a polycarbon/polycarbonate bonding and drying agent for concrete that may cure some new concrete uniformly while resisting spot drying and hair checking.

Advantages

- Does not alter color or texture of concrete
- Preserves most concrete surfaces
- One coat application
- Retards some hydrostatic head
- Reduces seepage
- Provides a prepared surface for paint, extending paint life
- Properly installed, provides excellent bonding between concrete slabs
- Permanently hardens and densifies concrete surfaces
- Prevents dusting

Applications

- Vertical & Horizontal Concrete Applications
- Existing Concrete
- New Concrete
- Between Concrete Slabs
- Bonding Agent for polycarbon/polycarbonate grouts & patches

Technical Support

For technical support: 800.349.7325 or information@prosealproducts.com

Instructions

1. Apply product using a simple 20-30 psi low-pressure sprayer at a coverage rate of 200-600 square feet per gallon depending on substrate.
2. In areas where seepage exists, Pro-Seal DP-36® may be required.
3. For specific application instructions or guide specifications, contact us at 800.349.7325 or information@prosealproducts.com

Technical

Information	Value
Material	1 part
Appearance	Liquid
Application	See guide specification
Application temp	> 42°F to <220°F
Storage temp	> 32°F to < 98°F
Coverage rate	200-600 ft ² / gallon
Dry time	2-4 hours
Packaging	Quart, 1 gallon, 5 gallons and 55 gallons

Cautions

Keep out of reach of children. May cause skin or eye irritation. May be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.



Pro-Seal Drycrete™

Polycarbon/Polycarbonate Bonding And Drying Agent



Pro-Seal Drycrete™

Limited Warranty

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal