



# Pro-Seal Flash Guard Tape™

## Polycarbon/Polycarbonate Peel-and-Stick Flashing Tape

### Product Description

**Pro-Seal Flash Guard Tape™** is a polycarbon/polycarbonate single component peel-and-stick sealer that is supplied as a rolled-good.

### Advantages

- Easy to install
- Provides Instant grip to a large variety of substrates
- Easily cut into any shape or length
- 100% solids rubber-like backing
- Seals on contact
- Self-adhering
- Conforms to almost any shape

### Applications

- Cracks
- Joints
- Penetrations
- Pipes
- Parapet walls
- Roofing
- HVAC ductwork
- Flashings
- Railways
- Metal roofs
- And more!

### Technical Support

Contact our technical dept. at 800.349.7325 or [information@prosealproducts.com](mailto:information@prosealproducts.com)

### Instructions

1. Surface must be dry, clean and free of all loose particulate and bond-breaking matter.
2. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 800.349.7325 or [information@prosealproducts.com](mailto:information@prosealproducts.com)

### Technical

Information	Value
Material	1 Part
Mix Time	N/A
Appearance	Rolled-Good
Application	See Guide Specification
Application Temp.	35°F To 220°F
Service Temp.	-20°F To 180°F
V.O.C.	None
Flash Point	N/A
Tensile Strength	570 psi
Peel Strength	10 Lbs /Per Linear Inch
Color	White & Gray
Solids	100%
Packaging:	4" X 50' Roll, 6" X 50' Roll or 12" X 50' Roll

### Cautions

Keep out of reach of children. May cause skin or eye irritation. May be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.



# Pro-Seal Flash Guard Tape™

*Polycarbon/Polycarbonate Peel-and-Stick Flashing Tape*



Pro-Seal Flash Guard Tape™

## **Limited Warranty**

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.



16541 Redmond Way • Suite 363C • Redmond, WA 98052  
Phone: 800.349.7325 • [information@prosealproducts.com](mailto:information@prosealproducts.com)  
[www.prosealproducts.com](http://www.prosealproducts.com) • © Copyright Pro-Seal