

**MATERIAL SAFETY DATA SHEET**

**WHMIS Hazard Classification: H F R P**

**Date: 9.1.08**

**SECTION I PRODUCT IDENTIFICATION**

**Product Identifier:** Power Kote Hydro Paint Rubberized  
**Product Use:** Paint/Coating.

**Supplier's Name:** Pro-Seal Products  
**Address:** 16541 Redmond Way Suite 363C  
 Redmond, WA 98052

**Emergency Number:** (800) 424-9300 **Information:** (800) 349-7325

**SECTION II HAZARDOUS INGREDIENT**

Compound	%	CAS#	LD <sub>50</sub> Species/Route	LC <sub>50</sub> Species/Route
Xylol / XYLENE	<30%	1330-20-7		100 ppm

**SECTION III PHYSICAL DATA**

**Odor & Appearance:** Clear OR PIGMENTED, mobile liquid with a SOLVENT odor.  
**Odor Threshold:** Liquid  
**Physical State:** N/A **Evaporation Rate:** Butyl Acetate = 1) =00.6  
**Specific Gravity:** .870 **Vapor Pressure:** (mm Hg) = 9.5  
**Vapor Density: (AIR = 1)** 3.7 **Freezing Point:** No data  
**Boiling Point (mmHg):** degrees F 278 **Solubility in Water:** Practically Insoluble  
**pH**

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

**Flash Point (Method):** TAG / Degrees F 82 **Flammability Limits In Air:** N/A  
 (Not material rating Flash Point)  
**Auto Ignition Temp:** **l.e.l:** 1.1 **u.e.l:** 6.6  
**Extinguishing Media:** Use carbon dioxide or dry chemical for small fires, aqueous foam (water will spread fire)  
**Special fire fighting Procedures:** Remove all ignition sources. Wear self contained breathing apparatus and complete personal protective equipment when entering confined areas where there is a potential of exposure to vapors or products of combustion.  
**Unusual Fire & Explosion Hazards:** Closed containers may rupture / explode in fire due to heat, spark or flame. Vapor will flash or explode if ignited. In fire keep cool with water spray or fog (water is not an extinguishing media). Empty containers present explosion hazard due to residual vapors.  
**Sensitivity to Static Discharge:**  
**Sensitivity to Impact:** N/A

**SECTION V REACTIVITY DATA**

**Stability:** Stable  
**Hazardous Decomposition Products:** Produced when heated to decomposition may include Carbon monoxide and Carbon Dioxide.  
**Incompatibility:** (Materials to avoid): Heat, Sparks, Open Flame  
**Hazardous Polymerization:** Will not occur.

SECTION VI TOXICOLOGICAL DATA

**Route of Entry:** inhalation, skin, Ingestion.

**Exposure Limits:**

**Over Exposure Symptoms:**

Skin or respiratory irritation. Signs of Central Nervous System (CNS) depression may be evidenced by giddiness, headache, dizziness, or nausea; extreme case labored breathing, cyanosis (blueskin palor); in severe cases death may occur.

**Effects of Acute Exposure and Effects of Chronic Exposure:** Vapors may be irritating to nose, throat and respiratory tract. High vapor concentrations may cause CNS depression.

**Skin:** Liquid is irritating to skin, prolonged or repeated contact may result in irritation and dermatitis.

**Ingestion:** may result in vomiting; avoid aspiration as it may result in aspiration pneumonitis.

**Carcinogenicity:** N/A

SECTION VII PREVENTATIVE MEASURES

**Respiratory Protection:** Positive airflow in well ventilated area with canister mask. Use self-contained breathing apparatus in areas of high vapor concentration.

**Ventilation:** Ventilate with positive airflow when possible use appropriate vapor mask.

**Protective Gloves:** Recommended

**Eye Protection:** Chemical or vapor proof safety goggles.

**Other Protective Equipment:** As required to avoid wetting of clothing or skin. Note: All equipment should be OSHA or NEOSHO approved.

**Leaks or Spill Procedures:** Remove all ignition sources, ventilate, do not inhale, use non-sparking tools, shut down spillage source, use absorbent material for collection.

**Waste Disposal:** Per federal, state, and local regulations, incinerate or other method.

**Precautions To Be Taken In Handling And Storage:** Sealed container in a cool place away from ignition sources.

**Storage Requirements:** per local regulations

SECTION VIII CONTROL MEASURES/PROTECTION INFORMATION

**Emergency and First Aid Procedures:**

Remove contaminated clothing/shoes, flush skin with copious amounts of water, followed by washing with soap and water. If irritation occurs contact a physician. Do not reuse clothing properly cleaned.

**Medical conditions aggravated by exposure:** Pre-existing eye, skinned respiratory disorders,

SECTION IX PREPARATION INFORMATION

Judgments as to the suitability of information herein for purchaser's purposes are necessarily purchaser's responsibility. Therefore, although reasonable care has been taken in the preparation of such information. Pro-Seal Systems Div ICP, Inc extends no warranties, makes no representations and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes of for consequences of its use.

Created By: MF