



Pro-Seal PC-V Kote™

Polycarbon/Polycarbonate Build-Up Coating

Product Description

Pro-Seal PC-V Kote™ is a polycarbon/polycarbonate single component build-up coating that will not support growth of major mold and mildew groups.

Advantages

- Easy to install
- Possesses high elongation qualities
- Excellent bridging ability
- Low temperature flexibility
- Resistant to many common chemicals and acids

Applications

- Exterior membrane for concrete pools
- Exterior building and waterproofing
- Joint membrane or corrugate steel, aluminum, transite, and miscellaneous other panel construction on roofs and sidewalls
- Elastic membrane roof coating on concrete domes, folded plate, and other contemporary designs
- Interior waterproofing where high tensile strength is needed
- Exterior waterproofing of most surfaces

Instructions

1. Surface must be dry, clean and free of all loose particulate and bond-breaking matter.
2. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 800.349.7325 or information@prosealproducts.com

Technical

Information	Value
Material	1 part
Mix time	N/A
Appearance	Liquid
Application	See guide specification
Solids	31.6% wt 20% vol
Elongation	200%
Build per coat	12-15 mils dry
Application temperature	-45°F to 140°F
Flash point	21°F open cup
Bridging ability	1/2 inch
Tensile strength	1,200 psi
Flexibility	180 bend of 1/8" mandrel at 30°F
Flammability	Will not support combustion
Temperature limits	108°F maximum
Coverage rate	30 sq. ft./gal @ 14 mils including bulking
Cure to touch	20 minutes
Full cure	72 hours
Packaging:	55 gallons

Technical Support

Contact our technical dept at 800.349.7325 or information@prosealproducts.com

Pro-Seal PC-V Kote™





Pro-Seal PC-V Kote™

Polycarbon/Polycarbonate Build-Up Coating

Cautions

Keep out of reach of children. May cause skin or eye irritation. May be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.

Pro-Seal PC-V Kote™



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal