

# Pro-Seal Power Kote Casting Grade™



*Polycarbon/Polycarbonate Casting & Entombment Material*

## Product Description

**Pro-Seal Power Kote Casting Grade™** is a polycarbon/polycarbonate three component casting or entombment material for reclaiming structural integrity after substrate degradation.

## Advantages

- Easy to install
- Use with Power Kote Injection Grade for increased structural integrity.
- Cast this product around a structure to maintain and or increase structural integrity as well as aesthetic quality

## Applications

- Use for structural casting repair in areas such as:
  - Foundations
  - Piers
  - Bridges
  - Cosmetic structural enhancement projects
  - Casting and entombment projects

## Instructions

1. Surface must be dry, clean and free of all loose particulate and bond-breaking matter.
2. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 800.349.7325 or [information@prosealproducts.com](mailto:information@prosealproducts.com)

## Technical

Information	Value
Material	3 part
Mix time	4-6 minutes
Appearance	Paste
Application	See guide specification
Pot life	1 hour
Flash point	500°F
Cure time to pull forms	6-96 hours
Full cure	96-144 hours
Stain resistance	Excellent
Packaging:	5 gallons or 55 gallons

## Technical Support

Contact our technical dept. at 800.349.7325 or [information@prosealproducts.com](mailto:information@prosealproducts.com)

## Cautions

Keep out of reach of children. May cause skin or eye irritation. May be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Pro-Seal Power Kote Casting Grade™



16541 Redmond Way • Suite 363C • Redmond, WA 98052  
Phone: 800.349.7325 • [information@prosealproducts.com](mailto:information@prosealproducts.com)  
[www.prosealproducts.com](http://www.prosealproducts.com) • © Copyright Pro-Seal

# Pro-Seal Power Kote Casting Grade™



*Polycarbon/Polycarbonate Casting & Entombment Material*

## Specifications

Test	Data	Value
ASTM D 695	Compressive strength	18,000 psi
ASTM D 1706	Cured hardness	82 shore d
ASTM D 790	Flexural strength	7,000 psi
ASTM D 1002	Adhesive tensile sheer	3,000 psi
ASTM D 638	Tensile strength	5,000 psi
ASTM D 2566	Cure shrinkage	.002 inches
Taber abrasion resistance	1,000 gm head cs 17 wheel wt loss 1,000 cycles	.00 mg
Taber abrasion resistance	1,000 gm head cs 17 wheel wt loss 350,000 cycles	.006 mg
FST 141 A	Method 4291 @ 75°F	5,00 cps

\* Data based on laboratory tested materials.

## Limited Warranty

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.

Pro-Seal Power Kote Casting Grade™

## Chemical Resistance

Cured material	Rating
Hydrochloric acid	Excellent
Sulfuric acid 60%	Fair
Nitric acid	Fair
Chromic acid	Fair
Kerosene	Excellent
Methanol	Very good
Toluene	Very good
Ammonia	Excellent
Nitrates	Fair
Sulfates	Very good
Phenol	Fair
Sodium hydroxide 10%	Excellent
Chlorinated solvent	Very good



16541 Redmond Way • Suite 363C • Redmond, WA 98052  
 Phone: 800.349.7325 • [information@prosealproducts.com](mailto:information@prosealproducts.com)  
[www.prosealproducts.com](http://www.prosealproducts.com) • © Copyright Pro-Seal