

# PROSEAL®

# Pro-Seal 34®

## PRODUCTS, INC.

**Pro-Seal 34® is a single component M34 elastoplastic, Polycarbon/Polycarbonate sealant material.** It stops leaks and seals on contact even through water and oil. Pro-Seal 34® is gunable from 38°F to 98°F and may be applied to surface temperatures ranging from -70°F to +220°F.

***Seals under water, through oil and to adhere kynar coated metals with no primer. Pro-Seal 34 has no memory, even when fully cured.***



#### COLORS

- Clear
- Black
- Brown
- White
- Gray

Available in 10.2 oz. Tube & 5 gallons

#### SEALS

- Galvanized metal
- Vinyl
- Plaster
- Wood
- And More!
- Stone
- Aluminum
- Concrete
- Recreational Vehicles

\* Not intended for bathrooms, exposed or traffic areas

#### ADVANTAGES

- Seals through rain and moving water
- Never gets hard or brittle
- 1200% elongation
- 350% stretch
- 2 year shelf life
- 6 month open tube life
- Paintable upon application
- Non-yellowing from UV rays



- **Accessible Sales & Technical Departments at 425.488.6570 or [information@prosealproducts.com](mailto:information@prosealproducts.com)**
- **Technologically Advanced Products that are green-friendly**

16541 Redmond Way • Suite 363C • Redmond, WA 98052

Phone: 425.488.6570 • Fax: 425.488.6926 • [prosealproducts.com](http://prosealproducts.com) • [information@prosealproducts.com](mailto:information@prosealproducts.com)