



Pro-Seal TVB Top Kote™

Polycarbon/Polycarbonate Vapor & Mold Control Coating

Pro-Seal TVB Top Kote™

Product Description

Pro-Seal TVB Top Kote™ is single component moisture cured top coating meant to be used in conjunction with Pro-Seal TVB Mastic™. This system is designed specifically for vapor and mold control.

System Advantages

- Designed to stop most vapor issues
- Prevents mold growth
- Multiple top coats may be applied within 7-12 hours of each other
- Excellent life-cycle economics
- Can be applied to wet concrete
- No mechanical profiling required
- Easy to repair or touch-up
- Excellent elongation and stretch
- Up to 30 year warranties available when installed by a certified applicator

Applications

- Interior concrete substrates in need of vapor and/or mold control:
 - High-traffic hallways
 - Retail spaces
 - Basements
 - Office facilities
 - Any area that will be covered with carpet or tile

Technical Support

Contact our technical dept. at 800.349.7325 or information@prosealproducts.com

Technical

Information	Value
Material	1 part
Mix time	N/A
Appearance	Liquid
Application	See guide specification
Tack-free cure time	7 hours
Recoat cure time	7-12 hours
Complete cure	72 hours
Spread rate	100 square feet per gallon 10.5 mils of film
Stain resistance	Excellent
Flash point	120°F
Storage temp	40°F – 110°F
Weight per gallon	9.7 lbs
Color	Tan or gray
Packaging	5 gallon or 55 gallon

Instructions

1. Surface must be clean and free of all loose particulate and bond-breaking matter.
2. For specific application instructions contact our Technical Department at 800.349.7325 or information@prosealproducts.com

Cautions

Keep out of reach of children. May cause skin or eye irritation. May be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal

Pro-Seal TVB Top Kote™



Polycarbon/Polycarbonate Vapor & Mold Control Coating

Specifications

Concrete Specimens Tested as Follows		
Test	Data	Value
ASTM D 412	Tensile shear	2,600 psi
ASTM D 412	Elongation	.03% vol
ASTM E 96	Vapor transmission 5 mils 30 mils Full system	.8 perms .04 perms .002 perms
ASTM D 2369	Solids content Content x vol Content x %	79% 73%
ASTM D 2240	Shore hardness	92 A
ASTM D 4060	Abrasion resistance	Passes
ASTM D 903	Adhesive peel	No peel from base
ASTM D 1499	Weatherometer 2,000 hours	No cracking, crazing, spalling, or softening

* Data based on laboratory tested materials.

Limited Warranty

We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.



16541 Redmond Way • Suite 363C • Redmond, WA 98052
Phone: 800.349.7325 • information@prosealproducts.com
www.prosealproducts.com • © Copyright Pro-Seal