

MATERIAL SAFETY DATA SHEET**WHMIS Hazard Classification: H F R P****Date: 9.1.08****SECTION I PRODUCT IDENTIFICATION****Product Identifier:** Pro-Seal Weathermaster
Product Use: Top Coat Sealer**Supplier's Name:** Pro-Seal Products
Address: 16541 Redmond Way Suite 363C
Redmond, WA 98052**Emergency Number:** (800) 424-9300**Information:** (800) 349-7325**SECTION II HAZARDOUS INGREDIENT**

Compound	%	CAS#	LD₅₀ Species/Route	LC₅₀ Species/Route
Mineral Spirits			500/PEL ppm	

SECTION III PHYSICAL DATA

Odor & Appearance:	Colorless with Aliphatic odor	Odor Threshold:	N/A
Physical State:	N/A	Evaporation Rate:	(Butil-1) Slower
Specific Gravity:	H ₂ O-1 Barrier Type B	Vapor Pressure:	mm Hg @ 68°F Less 2mm
Vapor Density:	Air-1 Heavier	Freezing Point:	N/A
Boiling Point:	340- 415	Solubility in Water:	Negligible
pH:	N/A		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method): 106°F T.C.C.	Flammability Limits: (100°C/212°F)
Auto Ignition Temp:	l.e.l: 0.9 u.e.l: 8.0
Extinguishing Media: Foam CO ₂ , dry chemical	
Special Fire Fighting Procedures: Wear MESA/NOISH approved self-contained breathing apparatus. Cool fire exposed containers with water spray. Solid stream of water will spread fire.	
Unusual Fire and Explosion Hazards: Products of combustion are toxic. Heated solvent vapors can travel to ignition source and flash back. Explosive mixtures can form with air.	
Sensitivity to Static Discharge: N/A	
Sensitivity to Impact: N/A	

SECTION V REACTIVITY DATA**Stability:** Yes
Incompatibility: Strong oxidizers
Hazardous Decomposition Products: Thermal
Hazardous Polymerization: N/A

SECTION VI TOXICOLOGICAL DATA

Route of Entry: Inhalation, Ingestion

Exposure Limits:

Effects of Acute Exposure: headache, nausea, nose, skin throat and lung irritation, EG may cause drowsiness, nausea and slurred speech.

Effects of Chronic Exposure: EG may cause dizziness, stupor, unconsciousness. Harmful if swallowed, can cause kidney damage, fatal in large doses.

Carcinogenicity, Reproductive Toxicity, Teratogenicity, Mutagenicity: Not listed as carcinogen.

Toxicologically Synergistic Products:

SECTION VII PREVENTATIVE MEASURES

Respiratory Protection: None if standard draft or ventilation is maintained. Do not breathe in over spray. Vapor mask should be used if there is no draft or ventilation.

Ventilation: Breeze or standard ventilation

Protective Gloves: Yes

Eye Protection: Yes, safety equipment should be worn on all application/construction (ANZI 2-8) sites.

Other Protective Equipment: Safety boots, pants, etc. (respirators should be MSHA/NOISH approved pressure demand)

Leak or Spill Procedures: Keep spectator from area. Dike and contain with inert material. Keep out of sewers. Re-contain and use or dispose if not usable.

Waste Disposal: Dispose of material solidifies with lime and ferric chloride and incinerate. Flush supernatant liquids to chemical sewer.

Precautions to be taken in Handling and Storage: Keep temps in greater than 1°C/34°F less than 49°C/120°F ranges.

Storage Requirements: Keep away from children.

SECTION VIII CONTROL MEASURES/PROTECTION INFORMATION

Emergency and First Aid Procedures:

Wash skin with soap and water if contact occurs.

Eye was facility/ safety showers recommended if acute or chronic exposure occurs for 15 minutes.

Inhalation: Move subject to fresh air. Artificial respiration if breathing stops.

Ingestion: Dilute by drinking water, do not induce vomiting, call a physician

SECTION IX PREPARATION INFORMATION

Judgments as to the suitability of information herein for purchaser's purposes are necessarily purchaser's responsibility. Therefore, although reasonable care has been taken in the preparation of such information. Pro-Seal Systems Div ICP, Inc extends no warranties, makes no representations and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes of for consequences of its use.

Created By: MF